BENCHMARK:

NATIONAL GEODETIC SURVEY MARKER DM7883, A 2 INCH IN DIAMETER GALVANIZED STEEL PIPE STATIC OPUS OBSERVATION ELEVATION = 127.59'.

PROJECT TBM:

'X' CUT ON TOP OF HEADWALL SOUTH SIDE OF DRIVEWAY ON WALLIS STREET INTO TEXANA. ELEVATION = 138.05'

FLOOD ZONE NOTES:

I HAVE EXAMINED THE FLOOD INSURANCE RATE MAP # 48157C0085M, DATED JANUARY 29, 2021 AND HAVE DETERMINED THAT THE PROJECT TRACT LIES WHOLLY WITHIN FLOOD ZONE 'X' AND DETERMINED TO BE OUTSIDE 500-YEAR FLOODPLAIN.

THIS INFORMATION IS TO BE USED TO DETERMINE FLOOD INSURANCE RATES ONLY, AND IS NOT INTENDED TO IDENTIFY SPECIFIC FLOOD CONDITIONS.


<u>NOTE:</u> DRIVING AISLE DIMENSIONS AS SHOWN ARE MEASURED FROM FACE OF CURB TO FACE OF CURB.

<u>NOTE:</u> ALL DIMENSIONS AND RADII FOR PAVEMENTS ARE MEASURED FROM BACK OF CURB.


NOTE: ALL CURB WIDTHS ARE 6" UNLESS OTHERWISE SPECIFIED

POLO RANCH, SEC. 11 18.372 ACS. CHURCHILL FULSHEAR LEAGUE, A–29 FBCCF NO. 20200228

20 G



PRECAST CONCRETE WHEEL STOP (TYPICAL)



FACE OF CURB WHEEL STOP (TYP.), CENTERED ON STALL 17'

8" 3⁄4"

9½"

STATION

TYPICAL STANDARD PARKING DETAIL WITH SIDEWALK N.T.S.

HANDICAP PARKING SIGN _ WALK WALK _____ _____ _____ 2' OVERHANG FACE OF CURB * ALL PERIMETER STRIPING FOR LOADING BAY 6" WIDE, DIAGONAL STRIPING 4" WIDE AT 45 DEG. SPACED 24" 4" WHITE STRIPPING PARKING* * ALL LETTERS TO BE CAPITAL WITH MINIMUM HEIGHT OF 12 INCHES & MINUMUM STROKE WIDTH OF 2 INCHES, IN WHITE COLOR, CENTERED WITHIN THE PARKING SPACES OR IN THE CROSS HATCH. VAN ACCESSIBLE TYPICAL HANDICAP PARKING DETAIL N.T.S.

