






PROPOSED LEGEND:	TYPICAL NEW CONSTRUCTION NOTES:
 EXISTING WALL TO REMAIN  EXISTING WINDOW TO REMAIN  EXISTING DOOR AND FRAME TO REMAIN  NEW WOOD STUD WALL  NEW DOOR AND FRAME	<ol style="list-style-type: none"> 1. DIMENSIONS NOTED "CLR" (CLEAR) ARE NOT ADJUSTABLE WITHOUT APPROVAL FROM THE ARCHITECT. 2. IF CONFLICTS OCCUR BETWEEN DRAWING AND EXISTING FIELD CONDITIONS, THE GENERAL CONTRACTOR SHALL IMMEDIATELY CONTACT THE ARCHITECT FOR DIRECTION. 3. ALL NEW PARTITIONS SHOWING ABUTTING TO EXISTING COLUMNS OR WALLS SHALL ALIGN WITH FACE OF EXISTING FINISHED SURFACE UNLESS OTHERWISE NOTED IN THE DRAWINGS. 4. CONTRACTOR TO PROPERLY PROTECT ANY AND ALL EXISTING AREAS TO REMAIN, REPAIRING ANY AND ALL DAMAGE TO EXISTING FINISHED SURFACES DURING CONSTRUCTION WILL BE THE RESPONSIBILITY OF THE CONTRACTOR. 5. PATCH AND FINISH EXISTING AREAS DISTURBED BY CONSTRUCTION OF NEW ARCHITECTURAL, ELECTRICAL, PLUMBING, AND MECHANICAL WORK. RESTORE AND REPAIR TO MATCH EXISTING ADJACENT AREA IN MATERIALS AND FINISH. 6. ALL EXISTING AND NEW PIPE AND CONDUIT PENETRATIONS THROUGH ANY FIRE RATED ASSEMBLY SHALL BE FIRESTOPPED WITH TESTED, LISTED, RATED THROUGH PENETRATION FIRE STOP SYSTEMS EXCEEDING THE REQUIRED RATINGS. 7. ANY EXISTING AND NEW DUCTWORK PENETRATIONS THROUGH ANY FIRE RATED ASSEMBLY SHALL INCLUDE A FIRE DAMPER, WHETHER SPECIFICALLY CALLED OUT IN THE DRAWINGS OR NOT. 8. ELECTRICIAN TO PROVIDE POWER / DATA AS REQUIRED. COORDINATE REQUIREMENTS W/ TENANT AND EQUIPMENT SELECTIONS.

