



Not Our Property

TRASH COMPACTOR ROOM
1. 3 HR WALLS 8" CONC BLOCK STC & L
2. ELEC. PWR. 3 PHASE 60 AMPS DEDICATED LINE
3. SPRINKLERS SHALL BE AUTOMATICALLY OPERATED
AT A TEMPERATURE NOT EXCEEDING 165 DEGREES F
4. REFUSE ROOM SHALL BE ONLY USED FOR REFUSE
AND REFUSE COMPACTING EQUIPMENT.

ALL EXISTING WALLS SHALL
INCLUDE THE INTERNATIONAL
FRAMING OF EXISTING WALLS
AND SHALL BE REINFORCED
WITH 2 #4 BARS @ 16" O.C.
ALL EXISTING WALLS SHALL
BE REINFORCED WITH 2 #4
BARS @ 16" O.C. THROUGH
THE ENTIRE THICKNESS OF
THE WALL.

COMMERCIAL 1
2561 SF

COMMERCIAL 2
1295 SF

COMMERCIAL 3
879 SF

CONC. CURB

CONC. SIDEWALK

X-140

X-120

X-100

X-80

X-60

X-40

X-20

X-10

X-0

X-140

X-120

X-100

X-80

X-60

X-40

X-20

X-10

X-0

3 A-210

3 A-202

4 A-210

B.B

A.A

3 A-210

3 A-202

4 A-210

B.B

A.A

A.A

Y-30

Y-50

Y-70

Y-90

Y-110

Y-130

Y-150

Y-170

TV-V13-6

TV-V13-6

BV-13-2

TV-V13-6

TV-V13-6

1

2

3

4

5

U

6.6

AA