



NOTE: TEMPORARY SEDIMENT TRAPS AND SLOPE PROTECTION SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION AND SHALL BE REMOVED AND THE AREA RESTORED TO ORIGINAL CONDITION IMMEDIATELY UPON COMPLETION OF CONSTRUCTION.

NOTE: TEMPORARY SEDIMENT TRAPS AND SLOPE PROTECTION SHALL BE INSTALLED AND MAINTAINED THROUGHOUT CONSTRUCTION AND SHALL BE REMOVED AND THE AREA RESTORED TO ORIGINAL CONDITION IMMEDIATELY UPON COMPLETION OF CONSTRUCTION.

EROSION CONTROL LEGEND:

- (TS) = TEMPORARY SEDIMENT TRAP (Practice No. 3.11)
 - (PS) = PERMANENT SEDIMENT TRAP (Practice No. 3.12)
 - (SF) = SLOPE PROTECTION (Practice No. 3.05)
 - (CE) = TEMPORARY STONE CONSTRUCTION ENTRANCE (Practice No. 3.02)
 - (SRS) = CONSTRUCTION ROAD STABILIZATION (Practice No. 3.03)
 - (CIP) = CLEARER ALLET PROTECTION (Practice No. 3.08)
 - (OP) = OUTLET PROTECTION (Practice No. 3.18)
 - (DD) = TEMPORARY DIVERSION DITCH (Practice No. 3.09)
 - (SR) = SURFACE REINFORCEMENT (Practice No. 3.20)
 - (ST) = TEMPORARY SEDIMENT TRAP (Practice No. 3.11)
- EXISTING CONTOUR
 — PROPOSED CONTOUR

EROSION CONTROL NOTES:

1. ALL VEGETATIVE AND STRUCTURAL EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE CONSTRUCTED AND MAINTAINED ACCORDING TO MINIMUM STANDARDS AND SPECIFICATIONS OF THE VIRGINIA DEPARTMENT OF TRANSPORTATION AND CONSTRUCTION DIVISION, REVISIONS 1982 EDITION, AND THE VIRGINIA REGULATORY BOARD 625-02-03 EROSION AND SEDIMENT CONTROL, REVISIONS 1982 EDITION.

2. PERMANENT MEASURES (DESIGN, CONSTRUCTION) SHALL BE INSTALLED WITHIN 7 DAYS OF THE DISTURBED AREA AND SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION.

3. MAINTENANCE: ALL EROSION AND SEDIMENT CONTROL MEASURES ARE TO BE INSPECTED BY THE FRUIT HOLDER WITHIN 24 HOURS OF A SIGNIFICANT RAINFALL. INSPECTION SHOULD BE IN AND CASE WATER SHALL BE REPORTED TO THE INSPECTION DIVISION. SEDIMENT WHICH WASHES TO LEAVE THE END OF THE DRAINAGE DISTRICT SHALL BE REMOVED IMMEDIATELY. SEDIMENT WHICH WASHES TO LEAVE THE END OF THE DRAINAGE DISTRICT SHALL BE REMOVED IMMEDIATELY. SEDIMENT WHICH WASHES TO LEAVE THE END OF THE DRAINAGE DISTRICT SHALL BE REMOVED IMMEDIATELY. SEDIMENT WHICH WASHES TO LEAVE THE END OF THE DRAINAGE DISTRICT SHALL BE REMOVED IMMEDIATELY.

4. PROPOSED DISTURBED AREA = 5.5 ACRES ±

NOTE: The existing topographic map was prepared by the U.S. Army Corps of Engineers, Hydrographic Survey, and is shown as a reference only.

SHEET NO. 1 OF 2	EROSION CONTROL PLAN	JOB NO. 03-082	DATE: JUNE 2, 2003	PREPARED BY PIEDMONT LAND SURVEYING, LLC 3416 VIRGINIA AVENUE SUITE 5 COLLINGSVILLE, VIRGINIA 24078 PHONE 276-647-4448 FAX 276-647-4252	PREPARED FOR FRITH CONSTRUCTION CO. PO DRAWER 5028 MARTINSVILLE, VIRGINIA 24115 PHONE 276-632-7241
SEDIMENT AND EROSION CONTROL PLAN FOR FRITH CONSTRUCTION CO. RIDGWAY DISTRICT, HENRY COUNTY, VIRGINIA					

